

Problem M. Please Save Pigeland

Input file: standard input
Output file: standard output
Time limit: 3 seconds
Memory limit: 1024 megabytes

Some horrible disease called Mysterious Oscar is spreading in Pigeland. The Pigeland has n cities and is connected by $n - 1$ bi-directional roads. The i -th road is connecting city u_i and city v_i , with length w_i . It is guaranteed that for every city it is possible to travel to any other city using these roads.

Now, there are k distinct cities c_1, c_2, \dots, c_k having the horrible disease. As the leader of the Pigeland, Putata and Budada are going to save the Pigeland. First they will find a city r to build up a hospital, without considering whether city r is infected by the disease. Then, they will use the rest of their money to build the only vehicle which could travel in Pigeland, the Piggigcar. Because they are strapped for cash, they can only build one Piggigcar, and once a Piggigcar is built, some parameter d of the Piggigcar is set, and could not be changed. The Piggigcar having parameter d can only travel from one city to the other, where the distance between the two cities should be a multiple of d . Formally, if you want to travel from city u to city v , the distance of the shortest path between u, v should be $p \times d$, where p is a non-negative integer, and this would cost p Pigecoins. Please notice that if you want to travel from city u to city v , it is **not necessary** to stop at every city on the path from u to v , the Piggigcar can directly go from u to v , if the minimum distance between u and v is a multiple of d .

For the following k days, Putata and Budada will take the following actions to save the Pigeland. On the i -th day, they will travel to city c_i from city r **along the shortest path** between city r and city c_i using the Piggigcar, cure all the piggies in the city and then travel back to city r from city c_i .

Putata and Budada want you to choose the proper city r to build the hospital, and the parameter d of the Piggigcar they should build, so that the Pigecoins spent during the travel is minimized. Please help them to find the minimum number of Pigecoins spent.

Input

The first line contains two integers n, k ($1 \leq n \leq 5 \times 10^5, 1 \leq k \leq n$), denoting the number of cities and the number of cities having disease.

The second line contains k distinct integers c_1, c_2, \dots, c_k ($1 \leq c_i \leq n$), denoting the cities having disease.

For the following $n - 1$ lines, each line contains three integers u, v, w ($1 \leq u, v \leq n, u \neq v, 1 \leq w \leq 10^7$), denoting a road connecting city u and v with length w .

It is guaranteed that you can go from any city to any other city using these roads.

Output

Output one integer in one line, denoting the minimum number of Pigecoins spent.

Example

standard input	standard output
5 3 3 4 5 1 2 2 2 3 4 2 5 4 3 4 6	8

Note

In the sample, you should choose city 1 to build hospital and build a Piggigcar with parameter 6, the

distance between city 1 and city 3, 4, 5 is 6, 12, 6, so the total Pigcoins costed is $1 \times 2 + 2 \times 2 + 1 \times 2 = 8$.